



SmartBright Floodlight G2 BVP151

BVP151 LED120/NW PSU 100W SWB G2 GM

SmartBright Floodlight G2 BVP151 - 12000 lm - 100 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

| General information | |
|--------------------------|---------------------------------|
| Light source color | 840 neutral white |
| Driver included | Yes |
| Optical cover/lens type | Glass |
| Control interface | - |
| Connection | Flying leads/wires |
| Cable | Cable 1.0 m without plug 3-pole |
| Protection class IEC | Safety class I |
| Flammability mark | - |
| CE mark | - |
| | |
| Operating and electrical | |
| Input Voltage | 220-240 V |
| Input Frequency | 50 or 60 Hz |
| Inrush current | 3.84 A |
| Power Factor (Min) | 0.95 |
| | |

| Controls and dimming | | |
|-------------------------------------|---|--|
| Dimmable | No | |
| | | |
| Mechanical and housing | | |
| Housing Material | Aluminum die-cast | |
| Optical cover/lens material | Tempered glass | |
| Overall length | 220 mm | |
| Overall width | 312 mm | |
| Overall height | 34.5 mm | |
| Effective projected area | 0.045 m² | |
| Color | Aluminum and gray | |
| | | |
| Approval and application | | |
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] | |
| Mech. impact protection code | IK08 [5 J vandal-protected] | |
| | | |
| Initial performance (IEC compliant) | | |
| Initial luminous flux (system flux) | 12000 lm | |

Datasheet, 2022, July 26 data subject to change

SmartBright Floodlight G2 BVP151


| Luminous flux tolerance | +/-10% |
|--------------------------------|------------------------|
| Initial LED luminaire efficacy | 120 lm/W |
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | >80 |
| Initial chromaticity | (0.380, 0.380) SDCM <5 |
| Initial input power | 100 W |
| Power consumption tolerance | +/-10% |
| | |

| Order product name | BVP151 LED120/NW PSU 100W SWB G2 GM |
|---------------------------------|-------------------------------------|
| EAN/UPC - Product | 8719514533998 |
| Order code | 911401856183 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 911401856183 |
| Copy Net Weight (Piece) | 1.740 kg |

| Application conditions | | — |
|---------------------------|-----------------|---|
| Ambient temperature range | -25 to +40 ℃ | |
| | | |
| Product data | | |
| Full product code | 871951453399899 | |



Dimensional drawing



BVP151 LED120/NW PSU 100W SWB G2 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.