



# SmartBright Floodlight G2 BVP151

## BVP151 LED180/CW PSU 150W SWB G2 CN

SmartBright Floodlight G2 BVP151 - 18000 lm - 150 W - 6500 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

### Product data

| General information     |                                 |
|-------------------------|---------------------------------|
| Light source color      | 865 cool daylight               |
| Driver included         | Yes                             |
| Optical cover/lens type | Glass                           |
| Control interface       | -                               |
| Connection              | Flying leads/wires              |
| Cable                   | Cable 1.0 m without plug 3-pole |
| Protection class IEC    | Safety class I                  |
| Flammability mark       | -                               |
| CE mark                 | -                               |

| Operating and electrical |             |
|--------------------------|-------------|
| Input Voltage            | 220-240 V   |
| Input Frequency          | 50 or 60 Hz |
| Inrush current           | 4.16 A      |
| Power Factor (Min)       | 0.95        |

| Controls and dimming |    |
|----------------------|----|
| Dimmable             | No |

| Mechanical and housing      |                      |
|-----------------------------|----------------------|
| Housing Material            | Aluminum die-cast    |
| Optical cover/lens material | Tempered glass       |
| Overall length              | 282 mm               |
| Overall width               | 409 mm               |
| Overall height              | 34.5 mm              |
| Effective projected area    | 0.077 m <sup>2</sup> |
| Color                       | Aluminum and gray    |

| Approval and application     |   |
|------------------------------|---|
| Ingress protection code      | IP65 [ Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [ 5 J vandal-protected]                  |

| Initial performance (IEC compliant) |          |
|-------------------------------------|----------|
| Initial luminous flux (system flux) | 18000 lm |

# SmartBright Floodlight G2 BVP151

|                                |                        |
|--------------------------------|------------------------|
| Luminous flux tolerance        | +/-10%                 |
| Initial LED luminaire efficacy | 120 lm/W               |
| Init. Corr. Color Temperature  | 6500 K                 |
| Init. Color Rendering Index    | >80                    |
| Initial chromaticity           | (0.313, 0.337) SDCM <5 |
| Initial input power            | 150 W                  |
| Power consumption tolerance    | +/-10%                 |

## Application conditions

|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -25 to +40 °C |
|---------------------------|---------------|


## Product data

|                   |                 |
|-------------------|-----------------|
| Full product code | 692382864856599 |
|-------------------|-----------------|

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Order product name              | BVP151 LED180/CW PSU 150W SWB G2 CN |
| EAN/UPC - Product               | 6923828648565                       |
| Order code                      | 911401867083                        |
| Numerator - Quantity Per Pack   | 1                                   |
| Numerator - Packs per outer box | 4                                   |
| Material Nr. (12NC)             | 911401867083                        |
| Net Weight (Piece)              | 2.740 kg                            |



## Dimensional drawing



BVP151 LED180/CW PSU 150W SWB G2 CN

