



SmartBright Floodlight G2 BVP151

BVP151 LED240/WW PSU 200W SWB G2 GM

SmartBright Floodlight G2 BVP151 - 22000 lm - 200 W - 3000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

General information	
Light source color	830 warm white
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-

Operating and electrical

Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	4.38 A
Power Factor (Min)	0.95

Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing Material	Aluminum die-cast	
Optical cover/lens material	Tempered glass	
Overall length	336 mm	
Overall width	482 mm	
Overall height	37.7 mm	
Effective projected area	0.112 m²	
Color	Aluminum and gray	
Approval and application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	22000 lm	

Initial luminous flux (system flux) 2

SmartBright Floodlight G2 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.440, 0.403) SDCM <5
Initial input power	200 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-25 to +40 °C


Order product name	BVP151 LED240/WW PSU 200W SWB G2 GM
EAN/UPC - Product	8719514534056
Order code	911401848183
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401848183
Net Weight (Piece)	4.160 kg

Product data

Full product code

871951453405699

Dimensional drawing



BVP151 LED240/WW PSU 200W SWB G2 GM



IP 65 K 08

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, July 26 - data subject to change