



SmartBright Floodlight G2 BVP151

BVP151 LED36/NW PSU 30W SWB G2 GM

SmartBright Floodlight G2 BVP151 - 3600 lm - 30 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

General information	
Light source color	840 neutral white
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	1.22 A
Power Factor (Min)	0.95

Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing Material	Aluminum die-cast	
Optical cover/lens material	Tempered glass	
Overall length	133 mm	
Overall width	182 mm	
Overall height	25.5 mm	
Effective projected area	0.017 m²	
Color	Aluminum and gray	
Approval and application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK07 [2 J reinforced]	
<u> </u>		
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	3600 lm	

Datasheet, 2022, July 26 data subject to change

SmartBright Floodlight G2 BVP151


Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	30 W
Power consumption tolerance	+/-10%

Order product name	BVP151 LED36/NW PSU 30W SWB G2 GM
EAN/UPC - Product	8719514534025
Order code	911401853183
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401853183
Net Weight (Piece)	0.610 kg

Application conditions		
Ambient temperature range	-25 to +40 °C	
Product data		
Full product code	871951453402599	



Dimensional drawing



BVP151 LED36/NW PSU 30W SWB G2 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.