



# SmartBright Floodlight G2 BVP151

# BVP151 LED60/NW PSU 50W SWB G2 GM

SmartBright Floodlight G2 BVP151 - 6000 lm - 50 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

## **Product data**

General information	
Light source color	840 neutral white
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-

#### Operating and electrical

220-240 V
50 or 60 Hz
1.68 A
0.95

Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing Material	Aluminum die-cast	
Optical cover/lens material	Tempered glass	
Overall length	173 mm	
Overall width	232 mm	
Overall height	26.1 mm	
Effective projected area	0.028 m²	
Color	Aluminum and gray	
Approval and application		
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK07 [ 2 J reinforced]	
Initial performance (IEC compliant)		
Initial luminaus fundame fund	6000 lm	

Initial luminous flux (system flux) 6000 lm

## SmartBright Floodlight G2 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	50 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-25 to +40 °C

871951453401899


Order product name	BVP151 LED60/NW PSU 50W SWB G2 GM
EAN/UPC - Product	8719514534018
Order code	911401854183
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401854183
Copy Net Weight (Piece)	0.910 kg



Product data Full product code

2

### **Dimensional drawing**



BVP151 LED60/NW PSU 50W SWB G2 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, July 26 - data subject to change