



# SmartBright Floodlight G2 BVP151

## BVP151 LED60/WW PSU 50W SWB G2 CN

SmartBright Floodlight G2 BVP151 – 5500 lm – 50 W – 3000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

### Product data

General information	
Light source color	830 warm white
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	1.68 A
Power Factor (Min)	0.95

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum die-cast
Optical cover/lens material	Tempered glass
Overall length	173 mm
Overall width	232 mm
Overall height	26.1 mm
Effective projected area	0.028 m <sup>2</sup>
Color	Aluminum and gray
Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	5500 lm

# SmartBright Floodlight G2 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.440, 0.403) SDCM <5
Initial input power	50 W
Power consumption tolerance	+/-10%

## Application conditions

Ambient temperature range	-25 to +40 °C
---------------------------	---------------


## Product data

Full product code	692382864970899
-------------------	-----------------

Order product name	BVP151 LED60/WW PSU 50W SWB G2 CN
EAN/UPC - Product	6923828649708
Order code	911401844083
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401844083
Net Weight (Piece)	0.850 kg



## Dimensional drawing



BVP151 LED60/WW PSU 50W SWB G2 CN

