



# SmartBright Floodlight G2 BVP151

## **BVP151 LED84/CW PSU 70W SWB G2 GM**

SmartBright Floodlight G2 BVP151 - 8400 lm - 70 W - 6500 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

#### **Product data**

General information	
Light source color	865 cool daylight
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	3.64 A
Power Factor (Min)	0.95

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum die-cast
Optical cover/lens material	Tempered glass
Overall length	203 mm
Overall width	284 mm
Overall height	29 mm
Effective projected area	0.038 m²
Color	Aluminum and gray
Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
Initial performance (IEC compl	iant)
Initial luminous flux (system flux)	8400 lm

Datasheet, 2022, July 26 data subject to change

# SmartBright Floodlight G2 BVP151


Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.313, 0.337) SDCM <5
Initial input power	70 W
Power consumption tolerance	+/-10%

Order product name	BVP151 LED84/CW PSU 70W SWB G2 GM
EAN/UPC - Product	8719514533929
Order code	911401865183
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401865183
Net Weight (Piece)	1.260 kg

Application conditions		
Ambient temperature range	-25 to +40 ℃	
Product data		
Full product code	871951453392999	



### Dimensional drawing



BVP151 LED84/CW PSU 70W SWB G2 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.