

Essential Smartbright waterproof

WT035C LED15/CW PSU GC CFW L600

Power supply unit - Beam angle 120° - Polycarbonate bowl/cover - 120° -

Essential Smartbright slim waterproof

Product data

General information	
Beam angle of light source	120 °
Light source color	865 cool daylight
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Beam angle 120°
Optical cover/lens type	Polycarbonate bowl/cover
Luminaire light beam spread	120°
Control interface	-
Connection	Connection unit 2-pole
Cable	Cable 0.25m without plug
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	CE mark
ENEC mark	-
Warranty period	2 years
Constant light output	No

Number of products on MCB of 16 A type B 24	
EU RoHS compliant	No
Light source engine type	LED

Operating and electrical

Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	2.5 A
Inrush time	0.1 ms
Power Factor (Min)	0.9

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-

Essential Smartbright waterproof

Optical cover/lens finish	Opal
Overall length	598 mm
Overall width	35.5 mm
Overall height	44.5 mm
Color	White

Approval and application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>70
Initial chromaticity	0.323 ; 0.35
Initial input power	15 W
Power consumption tolerance	+/-10%

Over time performance (IEC compliant)

Driver failure rate at 5000 h	0.004 %
-------------------------------	---------

Median useful life L70B50	20000 h
Median useful life L80B50	15610 h
Median useful life L90B50	7330 h

Application conditions


Ambient temperature range	-20 to +35 °C
Maximum dim level	Not applicable

Product data

Full product code	692382863428599
Order product name	WT035C LED15/CW PSU GC CFW L600
EAN/UPC - Product	6923828634285
Order code	911401820580
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401820580
Net Weight (Piece)	0.250 kg



Dimensional drawing



WT035C LED15/CW PSU GC CFW L600

