



GreenUp Waterproof

WT158C LED36S/840 PSU TW1 L1200 GM

_

GreenUp Waterproof is a high efficient and reliable LED luminaire, designed for industrial application with humid and dust protection requirement. It delivers significant energy savings of up to 62% as compared to conventional dual-T8 waterproof. Utilization of UV-shield PC and extrusion process makes it suitable for semi-outdoor environments, and together with the built-in breather ensure a sound performance. With professional optic design and Philips LED module gives the most comfortable light experience of CRI 85.

Product data

General information			
Light source color	840 neutral white		
Optical cover/lens type	-		
Control interface	-		
Protection class IEC	Safety class II		
CE mark	-		
Number of products on MCB of 16 A type B 1			
Light source engine type	LED		
Operating and electrical			
Input Voltage	220 to 240 V		
Input Frequency	50 or 60 Hz		
Power Factor (Min)	0.9		
Controls and dimming			
Dimmable	No		

Mechanical and housing	
Housing Material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Opal
Overall length	1258 mm
Overall width	69 mm
Overall height	90 mm
Color	Gray and white
Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W

Datasheet, 2022, August 10 data subject to change

GreenUp Waterproof

Init. Corr. Color Temperature	4000 K	
Init. Color Rendering Index	>80	
Initial input power	30 W	
Power consumption tolerance	+/-10%	
Application conditions		
Ambient temperature range	-20 to +45 °C	
Product data		

871016336315899


Order product name	WT158C LED36S/840 PSU TW1 L1200 GM
EAN/UPC - Product	8710163363158
Order code	911401895680
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401895680
Net Weight (Piece)	0.800 kg



Dimensional drawing

Full product code

WT158C



4200			٠			
LMOD		-		***	100 100	100-100
U300	-			1901	200 230	290 200
U900		**		1801	100 100	100-100

WT158C LED36S/840 PSU TW1 L1200 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.