



GreenUp Waterproof

WT158C LED36S/865 PSU TW1 L1200 GM

GreenUp Waterproof is a high efficient and reliable LED luminaire, designed for industrial application with humid and dust protection requirement. It delivers significant energy savings of up to 62% as compared to conventional dual–T8 waterproof. Utilization of UV-shield PC and extrusion process makes it suitable for semi-outdoor environments, and together with the built-in breather ensure a sound performance. With professional optic design and Philips LED module gives the most comfortable light experience of CRI 85.

Product data

General information		
Lamp colour code	865 cool daylight	
Optical cover/lens type	No [-]	
Control interface	-	
Protection class IEC	Safety class II (II)	
CE mark	-	
Number of products on MCB (16 A type B) 1		
Light source engine type	LED	
Operating and electrical		
Input Voltage	220 to 240 V	
Input frequency	50 or 60 Hz	
Power factor (min.)	0.9	
Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing material	Polycarbonate	
Optical cover/lens material	Polycarbonate	

Optical cover/lens finish	Opal
Overall length	1258 mm
Overall width	69 mm
Overall height	90 mm
Colour	Grey and White
Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80
Initial input power	30 W
Power consumption tolerance	+/-10%

Datasheet, 2022, August 10 data subject to change

GreenUp Waterproof


Application conditions	
Ambient temperature range	-20 to +45 ℃
Product data	
Full product code	871016336321999
Order product name	WT158C LED36S/865 PSU TW1 L1200 GM
EAN/UPC – product	8710163363219
Order code	911401896280


SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	911401896280
Net Weight (Piece)	0.800 kg



Dimensional drawing

WT158C





WT158C LED36S/865 PSU TW1 L1200 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.