



GreenUp Waterproof

WT158C LED56S/865 PSU TW1 L1500 GM

GreenUp Waterproof is a high efficient and reliable LED luminaire, designed for industrial application with humid and dust protection requirement. It delivers significant energy savings of up to 62% as compared to conventional dual–T8 waterproof. Utilization of UV-shield PC and extrusion process makes it suitable for semi-outdoor environments, and together with the built-in breather ensure a sound performance. With professional optic design and Philips LED module gives the most comfortable light experience of CRI 85.

Product data

General information				
Lamp colour code	865 cool daylight			
Optical cover/lens type	No [-]			
Control interface	-			
Protection class IEC	Safety class II (II)			
CE mark	-			
Number of products on MCB (16 A type B) 1				
Light source engine type	LED			
Operating and electrical				
Input Voltage	220 to 240 V			
Input frequency	50 or 60 Hz			
Power factor (min.)	0.9			
Controls and dimming				
Dimmable	No			
Mechanical and housing				
Housing material	Polycarbonate			
Optical cover/lens material	Polycarbonate			

Optical cover/lens finish	Opal			
Overall length	1558 mm			
Overall width	69 mm			
Overall height	90 mm			
Colour	Grey and White			
Approval and application				
Ingress protection code	IP66 [Dust penetration-protected, jet-pro			
Mech. impact protection code	IK08 [5 J vandal-protected]			
Initial performance (IEC compliant)				
Initial luminous flux (system flux)	5600 lm			
Luminous flux tolerance	+/-10%			
Initial LED luminaire efficacy	120 lm/W			
Lamp colour temperature	6500 K			
Colour Rendering Index	>80			
Initial input power	46 W			
Power consumption tolerance	+/-10%			

Datasheet, 2022, August 10 data subject to change

GreenUp Waterproof


Application conditions	
Ambient temperature range	−20 to +45 °C
Product data	
Full product code	871016336323399
Order product name	WT158C LED56S/865 PSU TW1 L1500 GM
EAN/UPC – product	8710163363233
Order code	911401896480

SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	911401896480
Net Weight (Piece)	1.000 kg



Dimensional drawing

WT158C



umac (um)		٠			
LM00	**		**	***	190 160
U 200			1901	200 230	100-100
UMM			1901	100 100	100-100

WT158C LED56S/865 PSU TW1 L1500 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.