



UNIBollard

BCP311 LED760/WW 15W 100-240V Cyl BK

UNIBollard - 760 lm - 15 W - 3000 K

UNIBollard is dedicated to light up public environments of park, buildings outside area, compound areas to bring you a more bright light in evening with the safety and convenience. Its graceful appearance is also a part of public scenery to beautify area you live.

Warnings and Safety

• Use additional surge protection device in electrical circuit for lighting wiring.

Product data

General information	
Light source color	830 warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover frosted
Control interface	-
Connection	Screw connection block 3-pole
Cable	Cable 0.3 m with connector 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Light source engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not
	serviceable
Light technical	
Standard tilt angle posttop	-

Operating and electrical	
Input Voltage	100 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Mounting device	Baseplate
Optical cover/lens finish	Frosted
Overall height	600 mm
Overall diameter	160 mm
Color	Black and aluminum
·	

Datasheet, 2022, August 8 data subject to change


UNIBollard

Approval and application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK06 [1J]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux) 760 lm		
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	40 lm/W	
Init. Corr. Color Temperature	3000 K	
Init. Color Rendering Index	>80	
Initial input power	15 W	
Power consumption tolerance	+/-10%	
Application conditions		
Ambient temperature range	-40 to +50 °C	

Product data	
Full product code	911401755272
Order product name	BCP311 LED760/WW 15W 100-240V Cyl BK
Order code	911401755272
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 4	
Material Nr. (12NC)	911401755272
Copy Net Weight (Piece)	2.500 kg



Dimensional drawing







BCP311 LED760/WW 15W 100-240V Cyl BK



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.