



# PowerBalance G4

## RC650B LED40S8 TWH W60L60

Power supply unit - Reflector - Polycarbonate - 100° x 100°

PowerBalance G4 (RC650 range) is a complete office lighting family which creates a modern, flexible, and comfortable environment that fosters creativity and innovation. It provides multiple control options (Interact office, Interact pro, POE) to make your office energy efficient and easy to manage.

### Product data

General information	
Beam angle of light source	120 °
Light source color	830 warm white and 865 cool daylight
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Reflector
Optical cover/lens type	Polycarbonate
Luminaire light beam spread	100° x 100°
Control interface	DALI
Connection	Screw connection block 3-pole
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	80

EU RoHS compliant	Yes
Light source engine type	LED

Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	N.A. W
Average CLO power consumption	N.A. W
Inrush current	12 A
Inrush time	50 ms
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing Material	Steel
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate

## PowerBalance G4

Fixation material	Steel
Optical cover/lens finish	Textured
Overall length	597 mm
Overall width	597 mm
Overall height	70 mm
Color	White

### Approval and application

Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK03 [ 0.3 J]

### Initial performance (IEC compliant)

Initial luminous flux (system flux)	4100 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	136.7 lm/W
Init. Corr. Color Temperature	-
Init. Color Rendering Index	>80
Initial chromaticity	SDCM<3
Initial input power	30 W
Power consumption tolerance	+/-10%

### Over time performance (IEC compliant)

Median useful life L70B50	50000 h
Median useful life L80B50	50000 h
Median useful life L90B50	33817 h

### Application conditions


Ambient temperature range	-20 to +40 °C
Maximum dim level	1%
Suitable for random switching	No

### Product data

Full product code	911401554061
Order product name	RC650B LED40S8 TWH W60L60
Order code	911401554061
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401554061
Net Weight (Piece)	5.299 kg



## Dimensional drawing



RC650B LED40S8 TWH W60L60

