



GreenUp hospitality spot

RS318B P5 927 PSU-E NB D

GreenUp hospitality spot is a small cut out spot but with comprehensive offers. It offers flexible wattages for different indoor applications, such as retail and hospitality. This family delivers high CRI90 and 3 different beam angles to perfectly fit the light requirement of indoor retail and hospitality applications.

Product data

| General information | |
|--|-----------------|
| Light source color | 927 warm white |
| Optical cover/lens type | - |
| Control interface | - |
| Protection class IEC | Safety class II |
| Flammability mark | - |
| CE mark | - |
| Number of products on MCB of 16 A type B | - |
| Light source engine type | LED |
| Operating and electrical | |
| Input Voltage | 220 to 240 V |
| Input Frequency | 0/50/60 Hz |
| Inrush current | 0.025 A |
| Power Factor (Min) | 0.9 |

| Controls and dimming | |
|------------------------------|---------------------------|
| Dimmable | No |
| Mechanical and housing | |
| Housing Material | Aluminum die-cast |
| Optical cover/lens material | Polycarbonate |
| Optical cover/lens finish | Clear |
| Overall length | 93 mm |
| Overall width | 85 mm |
| Overall height | 93 mm |
| Overall diameter | 85 mm |
| Color | Aluminum and gray |
| Approval and application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK03 [0.35 J reinforced] |

GreenUp hospitality spot

Initial performance (IEC compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 400 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 96 lm/W |
| Init. Corr. Color Temperature | 2700 K |
| Init. Color Rendering Index | >90 |
| Initial chromaticity | - |
| Initial input power | 5 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -20 to +40 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|--------------------------|
| Order product name | RS318B P5 927 PSU-E NB D |
| Order code | 911401502832 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 16 |
| Material Nr. (12NC) | 911401502832 |
| Net Weight (Piece) | 0.015 kg |



Dimensional drawing



RS318B P5 927 PSU-E NB D

