



# GreenUp hospitality spot

RS318B P7 927 PSD-E NB D

GreenUp hospitality spot is a small cut out spot but with comprehensive offers. It offers flexible wattages for different indoor applications, such as retail and hospitality. This family delivers high CRI90 and 3 different beam angles to perfectly fit the light requirement of indoor retail and hospitality applications.

## Product data

General information		Controls and dimming	
Light source color	927 warm white	Dimmable	Yes
Optical cover/lens type	-	<b>Mechanical and housing</b>	
Control interface	DALI	Housing Material	Aluminum die-cast
Protection class IEC	Safety class II	Optical cover/lens material	Polycarbonate
Flammability mark	-	Optical cover/lens finish	Clear
CE mark	-	Overall length	93 mm
Number of products on MCB of 16 A type B	-	Overall width	85 mm
Light source engine type	LED	Overall height	93 mm
<b>Operating and electrical</b>		Overall diameter	85 mm
Input Voltage	220 to 240 V	Color	Aluminum and gray
Input Frequency	0/50/60 Hz	<b>Approval and application</b>	
Inrush current	0.037 A	Ingress protection code	IP20 [ Finger-protected]
Power Factor (Min)	0.85	Mech. impact protection code	IK03 [ 0.35 J reinforced]

## GreenUp hospitality spot

### Initial performance (IEC compliant)

Initial luminous flux (system flux)	490 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	96 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	>90
Initial chromaticity	-
Initial input power	7 W
Power consumption tolerance	+/-10%

### Application conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

### Product data

Order product name	RS318B P7 927 PSD-E NB D
Order code	911401508132
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401508132
Net Weight (Piece)	0.021 kg



## Dimensional drawing



RS318B P7 927 PSD-E NB D

