



GreenUp hospitality spot

RS318B P7 930 PSD-E NB D

GreenUp hospitality spot is a small cut out spot but with comprehensive offers. It offers flexible wattages for different indoor applications, such as retail and hospitality. This family delivers high CRI90 and 3 different beam angles to perfectly fit the light requirement of indoor retail and hospitality applications.

Product data

General information	
Light source color	930 warm white
Optical cover/lens type	-
Control interface	DALI
Protection class IEC	Safety class II
Flammability mark	-
CE mark	-
Number of products on MCB of 16 A type B	-
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	0/50/60 Hz
Inrush current	0.037 A
Power Factor (Min)	0.85

Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Housing Material	Aluminum die-cast
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Overall length	93 mm
Overall width	85 mm
Overall height	93 mm
Overall diameter	85 mm
Color	Aluminum and gray
Approval and application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.35 J reinforced]

GreenUp hospitality spot

Initial performance (IEC compliant)

Initial luminous flux (system flux)	490 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	101 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>90
Initial chromaticity	-
Initial input power	7 W
Power consumption tolerance	+/-10%

Application conditions

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product data

Order product name	RS318B P7 930 PSD-E NB D
Order code	911401507832
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401507832
Net Weight (Piece)	0.021 kg



Dimensional drawing



RS318B P7 930 PSD-E NB D

