



GreenUp hospitality spot

RS318B P9 927 PSR-E MB D

GreenUp hospitality spot is a small cut out spot but with comprehensive offers. It offers flexible wattages for different indoor applications, such as retail and hospitality. This family delivers high CRI90 and 3 different beam angles to perfectly fit the light requirement of indoor retail and hospitality applications.

Product data

General information		Controls and dimming	
Light source color	927 warm white	Dimmable	Yes
Optical cover/lens type	-	Mechanical and housing	
Control interface	depends on driver (1-10V, DALI...)	Housing Material	Aluminum die-cast
Protection class IEC	Safety class II	Optical cover/lens material	Polycarbonate
Flammability mark	-	Optical cover/lens finish	Clear
CE mark	-	Overall length	93 mm
Number of products on MCB of 16 A type B	-	Overall width	85 mm
Light source engine type	LED	Overall height	93 mm
Operating and electrical		Overall diameter	85 mm
Input Voltage	220 to 240 V	Color	Aluminum and gray
Input Frequency	0/50/60 Hz	Approval and application	
Inrush current	0.045 A	Ingress protection code	IP20 [Finger-protected]
Power Factor (Min)	0.9	Mech. impact protection code	IK03 [0.35 J reinforced]

GreenUp hospitality spot

Initial performance (IEC compliant)

Initial luminous flux (system flux)	630 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	96 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	>90
Initial chromaticity	-
Initial input power	9 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Product data

Order product name	RS318B P9 927 PSR-E MB D
Order code	911401506232
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401506232
Net Weight (Piece)	0.021 kg



Dimensional drawing



RS318B P9 927 PSR-E MB D

