



# GreenUp hospitality spot

RS318B P9 930 PSU-E MB D

GreenUp hospitality spot is a small cut out spot but with comprehensive offers. It offers flexible wattages for different indoor applications, such as retail and hospitality. This family delivers high CRI90 and 3 different beam angles to perfectly fit the light requirement of indoor retail and hospitality applications.

## Product data

| General information                      |                 |
|--|-----------------|
| Light source color                       | 930 warm white  |
| Optical cover/lens type                  | -               |
| Control interface                        | -               |
| Protection class IEC                     | Safety class II |
| Flammability mark                        | -               |
| CE mark                                  | -               |
| Number of products on MCB of 16 A type B | -               |
| Light source engine type                 | LED             |
| Operating and electrical                 |                 |
| Input Voltage                            | 220 to 240 V    |
| Input Frequency                          | 0/50/60 Hz      |
| Inrush current                           | 0.045 A         |
| Power Factor (Min)                       | 0.9             |

| Controls and dimming         |                           |
|------------------------------|---------------------------|
| Dimmable                     | No                        |
| Mechanical and housing       |                           |
| Housing Material             | Aluminum die-cast         |
| Optical cover/lens material  | Polycarbonate             |
| Optical cover/lens finish    | Clear                     |
| Overall length               | 93 mm                     |
| Overall width                | 85 mm                     |
| Overall height               | 93 mm                     |
| Overall diameter             | 85 mm                     |
| Color                        | Aluminum and gray         |
| Approval and application     |                           |
| Ingress protection code      | IP20 [ Finger-protected]  |
| Mech. impact protection code | IK03 [ 0.35 J reinforced] |

## GreenUp hospitality spot

### Initial performance (IEC compliant)

|                                     |          |
|-------------------------------------|----------|
| Initial luminous flux (system flux) | 490 lm   |
| Luminous flux tolerance             | +/-10%   |
| Initial LED luminaire efficacy      | 101 lm/W |
| Init. Corr. Color Temperature       | 3000 K   |
| Init. Color Rendering Index         | >90      |
| Initial chromaticity                | -        |
| Initial input power                 | 9 W      |
| Power consumption tolerance         | +/-10%   |

### Application conditions


|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -20 to +40 °C |
|---------------------------|---------------|

### Product data

|                                 |                          |
|---------------------------------|--------------------------|
| Order product name              | RS318B P9 930 PSU-E MB D |
| Order code                      | 911401504432             |
| Numerator - Quantity Per Pack   | 1                        |
| Numerator - Packs per outer box | 16                       |
| Material Nr. (12NC)             | 911401504432             |
| Net Weight (Piece)              | 0.015 kg                 |



## Dimensional drawing



RS318B P9 930 PSU-E MB D

