



GreenPerform cleanroom recessed

CR468B LED55/NW PSU W60L60

Polycarbonate

GreenPerform cleanroom recessed is a family of cleanroom luminaires offering an energy efficient, long lasting and reliable lighting solutions for specialized applications. This family is designed for providing illumination for application areas in semiconductor industries, pharmaceutical industries, etc. GreenPerform cleanroom recessed family provides a lighting solution with excellent energy performance, long reliable lifetime, well protected against ingress of dust and moisture while contributing to a healthy and comfortable working environment.

Product data

General information	
Light source color	840 neutral white
Optical cover/lens type	Polycarbonate
Control interface	-
Protection class IEC	Safety class I
Flammability mark	-
CE mark	CE mark
Number of products on MCB of 16 A type B	24
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	19 A

Power Factor (Min)	0.9	
Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing Material	Metal	
Optical cover/lens material	Polycarbonate	
Optical cover/lens finish	Smoke	
Overall length	597 mm	
Overall width	597 mm	
Overall height	58 mm	
Overall diameter	597 mm	
Effective projected area	0.36 m²	

Datasheet, 2023, January 9 data subject to change


GreenPerform cleanroom recessed

Color	White RAL 9003
Approval and application	
Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK03 [0.3 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	5500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	106 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	5
Initial input power	52 W
Power consumption tolerance	+/-10%

Application conditions	
Ambient temperature range	+20 to +35 ℃
Product data	
Full product code	911401880099
Order product name	CR468B LED55/NW PSU W60L60
Order code	911401880099
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401880099
Net Weight (Piece)	6.999 kg



Dimensional drawing



CR468B LED55/NW PSU W60L60



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.