PHILIPS Lighting



GreenSpace linear accent

RS386B S10 P20 940 PSU-E WB WH

Polycarbonate cover and gloss high-reflective optic -

GreenSpace Linear accent is a comprehensive product offer with multiple modules available. By means of its modular design, it offers flexible lumen output for different indoor applications, such as office, retail and hospitality. This family provides both surface mounted and recessed installations with high CRI90 and 3 different beam angles to perfectly fit the light requirement of the indoor applications. Dali and 1-10V control interfaces give the way for future system connections as well.

Product data

| General information | | |
|---|-------------------------------------|--|
| Light source color | 940 neutral white | |
| Optical cover/lens type | Polycarbonate cover and gloss high- | |
| | reflective optic | |
| Control interface | - | |
| Protection class IEC | Safety class II | |
| CE mark | - | |
| Number of products on MCB of 16 A type B 25 | | |
| Light source engine type | LED | |
| | | |
| Operating and electrical | | |
| Input Voltage | 220 to 240 V | |
| Input Frequency | 50 or 60 Hz | |
| Power Factor (Min) | 0.9 | |
| | | |
| | | |

| Controls and dimming | |
|-------------------------------------|--------------------------|
| Dimmable | No |
| | |
| Mechanical and housing | |
| Housing Material | Aluminum Alloy |
| Optical cover/lens material | Polycarbonate |
| Optical cover/lens finish | Matte |
| Color | Black and white |
| | |
| Approval and application | |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| | |
| Initial performance (IEC compliant) | |
| Initial luminous flux (system flux) | 1150 lm |
| Luminous flux tolerance | +/-10% |

GreenSpace linear accent

| Initial LED luminaire efficacy | 65 lm/W |
|--------------------------------|---------------|
| Init. Corr. Color Temperature | 4000 K |
| Init. Color Rendering Index | >90 |
| Initial input power | 18 W |
| Power consumption tolerance | +/-10% |
| | |
| Application conditions | |
| Ambient temperature range | -20 to +40 °C |
| | |

RS386B S10 P20 940 PSU-E WB WH


| Order code | 911401512202 |
|---------------------------------|--------------|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 10 |
| Material Nr. (12NC) | 911401512202 |
| Copy Net Weight (Piece) | 0.450 kg |
| | |



Product data

Order product name

Dimensional drawing



RS386B S10 P20 940 PSU-E WB WH



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2022, July 12 - data subject to change