



# GreenUp Track

## ST306T P10 930 PSD NB WH SR

### Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

### Product data

General information		Optical cover/lens material	
Light source color	930 warm white	Optical cover/lens material	Polycarbonate
Optical cover/lens type	Lens	Optical cover/lens finish	Smoke
Control interface	depends on driver (1-10V, DALI...)	Overall length	150 mm
Protection class IEC	Safety class I	Overall width	95 mm
CE mark	-	Overall height	200 mm
Number of products on MCB of 16 A type B	210	Color	White
Light source engine type	LED	<b>Approval and application</b>	
<b>Operating and electrical</b>		Ingress protection code	IP20 [ Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [ 0.3 J]
Input Frequency	50 or 60 Hz	<b>Initial performance (IEC compliant)</b>	
Power Factor (Min)	0.9	Initial luminous flux (system flux)	850 lm
<b>Controls and dimming</b>		Luminous flux tolerance	+/-10%
Dimmable	Yes	Initial LED luminaire efficacy	85 lm/W
<b>Mechanical and housing</b>		Init. Corr. Color Temperature	3000 K
Housing Material	Aluminum die cast	Init. Color Rendering Index	>90
		Initial input power	10 W

## GreenUp Track

Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +40 °C
<b>Product data</b>	
Order product name	ST306T P10 930 PSD NB WH SR
Order code	911401541722

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401541722
Net Weight (Piece)	1.042 kg



## Dimensional drawing



ST306T P10 930 PSD NB WH SR

