



# GreenUp Track

ST306T P10 940 PSU NB WH BR

## Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

## Product data

General information	
Light source color	940 neutral white
Optical cover/lens type	Lens
Control interface	-
Protection class IEC	Safety class II
CE mark	-
Number of products on MCB of 16 A type B	210
Light source engine type	LED
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum die cast

Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Smoke
Overall length	150 mm
Overall width	95 mm
Overall height	185 mm
Color	White

Approval and application	
Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK03 [ 0.3 J]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	900 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>90
Initial input power	10 W


## GreenUp Track

Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +40 °C
<b>Product data</b>	
Order product name	ST306T P10 940 PSU NB WH BR
Order code	911401526722

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401526722
Net Weight (Piece)	1.035 kg



## Dimensional drawing



ST306T P10 940 PSU NB WH BR

