



GreenUp Track

ST306T P20 940 PSD NB BK SR

Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

| General information | | Optical cover/lens material | |
|------------------------------------------|------------------------------------|-------------------------------------|--------------------------|
| Light source color | 940 neutral white | Optical cover/lens material | Polycarbonate |
| Optical cover/lens type | Lens | Optical cover/lens finish | Smoke |
| Control interface | depends on driver (1-10V, DALI...) | Overall length | 150 mm |
| Protection class IEC | Safety class I | Overall width | 95 mm |
| CE mark | - | Overall height | 200 mm |
| Number of products on MCB of 16 A type B | 104 | Color | Black |
| Light source engine type | LED | | |
| Operating and electrical | | Approval and application | |
| Input Voltage | 220-240 V | Ingress protection code | IP20 [Finger-protected] |
| Input Frequency | 50 or 60 Hz | Mech. impact protection code | IK03 [0.3 J] |
| Power Factor (Min) | 0.9 | | |
| Controls and dimming | | Initial performance (IEC compliant) | |
| Dimmable | Yes | Initial luminous flux (system flux) | 1800 lm |
| | | Luminous flux tolerance | +/-10% |
| | | Initial LED luminaire efficacy | 90 lm/W |
| | | Init. Corr. Color Temperature | 4000 K |
| | | Init. Color Rendering Index | >90 |
| | | Initial input power | 20 W |
| Mechanical and housing | | | |
| Housing Material | Aluminum die cast | | |

GreenUp Track

| | |
|-------------------------------|-----------------------------|
| Power consumption tolerance | +/-10% |
| Application conditions | |
| Ambient temperature range | -20 to +40 °C |
| Product data | |
| Order product name | ST306T P20 940 PSD NB BK SR |
| Order code | 911401574422 |

| | |
|---------------------------------|--------------|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 911401574422 |
| Net Weight (Piece) | 1.042 kg |



Dimensional drawing



ST306T P20 940 PSD NB BK SR

