



# GreenUp Track

## ST306T P20 940 PSD NB WH SR

### Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

### Product data

General information	
Light source color	940 neutral white
Optical cover/lens type	Lens
Control interface	depends on driver (1-10V, DALI...)
Protection class IEC	Safety class I
CE mark	-
Number of products on MCB of 16 A type B	104
Light source engine type	LED

  

Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9

  

Controls and dimming	
Dimmable	Yes

  

Mechanical and housing	
Housing Material	Aluminum die cast

Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Smoke
Overall length	150 mm
Overall width	95 mm
Overall height	200 mm
Color	White

Approval and application	
Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK03 [ 0.3 J]

Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1800 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>90
Initial input power	20 W

## GreenUp Track

Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +40 °C
<b>Product data</b>	
Order product name	ST306T P20 940 PSD NB WH SR
Order code	911401545622

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401545622
Net Weight (Piece)	1.042 kg



## Dimensional drawing



ST306T P20 940 PSD NB WH SR

