



GreenUp Track

ST306T P28 940 PSR 1-10V NB WH BR

Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

General information	
Light source color	940 neutral white
Optical cover/lens type	Lens
Control interface	depends on driver (1-10V, DALI..)
Protection class IEC	Safety class I
CE mark	-
Number of products on MCB of 16 A type B	75
Light source engine type	LED
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Housing Material	Aluminum die cast

Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Smoke
Overall length	115 mm
Overall width	175 mm
Overall height	200 mm
Color	White


Approval and application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]


Initial performance (IEC compliant)

Initial luminous flux (system flux)	2800 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>90
Initial input power	28 W

GreenUp Track

Power consumption tolerance	+/-10%	Numerator - Quantity Per Pack	1
Application conditions		Numerator - Packs per outer box	8
Ambient temperature range	-20 to +40 °C	Material Nr. (12NC)	911401536622
Product data		Net Weight (Piece)	1.040 kg
Order product name	ST306T P28 940 PSR 1-10V NB WH BR		
Order code	911401536622		

Dimensional drawing



ST306T P28 940 PSR 1-10V NB WH BR

