



GreenUp Track

ST306T P30 930 PSD NB BK BR

Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

| General information | | Optical cover/lens material | |
|--|------------------------------------|--|--------------------------|
| Light source color | 930 warm white | Optical cover/lens material | Polycarbonate |
| Optical cover/lens type | Lens | Optical cover/lens finish | Smoke |
| Control interface | depends on driver (1-10V, DALI...) | Overall length | 175 mm |
| Protection class IEC | Safety class I | Overall width | 115 mm |
| CE mark | - | Overall height | 200 mm |
| Number of products on MCB of 16 A type B | 70 | Color | Black |
| Light source engine type | LED | Approval and application | |
| Operating and electrical | | Ingress protection code | IP20 [Finger-protected] |
| Input Voltage | 220-240 V | Mech. impact protection code | IK03 [0.3 J] |
| Input Frequency | 50 or 60 Hz | Initial performance (IEC compliant) | |
| Power Factor (Min) | 0.9 | Initial luminous flux (system flux) | 2700 lm |
| Controls and dimming | | Luminous flux tolerance | +/-10% |
| Dimmable | Yes | Initial LED luminaire efficacy | 90 lm/W |
| Mechanical and housing | | Init. Corr. Color Temperature | 3000 K |
| Housing Material | Aluminum die cast | Init. Color Rendering Index | >90 |
| | | Initial input power | 30 W |

GreenUp Track

| | |
|-------------------------------|-----------------------------|
| Power consumption tolerance | +/-10% |
| Application conditions | |
| Ambient temperature range | -20 to +40 °C |
| Product data | |
| Order product name | ST306T P30 930 PSD NB BK BR |
| Order code | 911401563322 |

| | |
|---------------------------------|--------------|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |
| Material Nr. (12NC) | 911401563322 |
| Net Weight (Piece) | 1.116 kg |



Dimensional drawing



ST306T P30 930 PSD NB BK BR

