



GreenUp Track

ST306T P38 940 PSR 1-10V MB WH SR

Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

General information		Optical cover/lens material	
Light source color	940 neutral white	Optical cover/lens material	Polycarbonate
Optical cover/lens type	Lens	Optical cover/lens finish	Smoke
Control interface	depends on driver (1-10V, DALI..)	Overall length	115 mm
Protection class IEC	Safety class I	Overall width	175 mm
CE mark	-	Overall height	200 mm
Number of products on MCB of 16 A type B	55	Color	White
Light source engine type	LED	Approval and application	
Operating and electrical		Ingress protection code	IP20 [Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [0.3 J]
Input Frequency	50 or 60 Hz	Initial performance (IEC compliant)	
Power Factor (Min)	0.9	Initial luminous flux (system flux)	3800 lm
Controls and dimming		Luminous flux tolerance	+/-10%
Dimmable	Yes	Initial LED luminaire efficacy	100 lm/W
Mechanical and housing		Init. Corr. Color Temperature	4000 K
Housing Material	Aluminum die cast	Init. Color Rendering Index	>90
		Initial input power	38 W

GreenUp Track

Power consumption tolerance	+/-10%
-----------------------------	--------

Application conditions

Ambient temperature range	-20 to +40 °C
---------------------------	---------------


Product data

Order product name	ST306T P38 940 PSR 1-10V MB WH SR
Order code	911401554722

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	911401554722
Net Weight (Piece)	1.040 kg



Dimensional drawing



ST306T P38 940 PSR 1-10V MB WH SR

