



GreenUp Track

ST306T P38 940 PSR 1-10V NB WH BR

Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

General information		Optical cover/lens material	
Light source color	940 neutral white	Optical cover/lens material	Polycarbonate
Optical cover/lens type	Lens	Optical cover/lens finish	Smoke
Control interface	depends on driver (1-10V, DALI..)	Overall length	115 mm
Protection class IEC	Safety class I	Overall width	175 mm
CE mark	-	Overall height	200 mm
Number of products on MCB of 16 A type B	55	Color	White
Light source engine type	LED		
Operating and electrical		Approval and application	
Input Voltage	220-240 V	Ingress protection code	IP20 [Finger-protected]
Input Frequency	50 or 60 Hz	Mech. impact protection code	IK03 [0.3 J]
Power Factor (Min)	0.9		
Controls and dimming		Initial performance (IEC compliant)	
Dimmable	Yes	Initial luminous flux (system flux)	3800 lm
		Luminous flux tolerance	+/-10%
		Initial LED luminaire efficacy	100 lm/W
		Init. Corr. Color Temperature	4000 K
		Init. Color Rendering Index	>90
		Initial input power	38 W
Mechanical and housing			
Housing Material	Aluminum die cast		


GreenUp Track

Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-20 to +40 °C
Product data	
Order product name	ST306T P38 940 PSR 1-10V NB WH BR
Order code	911401540222

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	911401540222
Net Weight (Piece)	1.040 kg



Dimensional drawing



ST306T P38 940 PSR 1-10V NB WH BR

