



# GreenUp Track

## ST306T P40 940 PSD NB BK BR

### Lens

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

### Product data

General information		Optical cover/lens material	
Light source color	940 neutral white	Optical cover/lens material	Polycarbonate
Optical cover/lens type	Lens	Optical cover/lens finish	Smoke
Control interface	depends on driver (1-10V, DALI...)	Overall length	175 mm
Protection class IEC	Safety class I	Overall width	115 mm
CE mark	-	Overall height	200 mm
Number of products on MCB of 16 A type B	51	Color	Black
Light source engine type	LED	<b>Approval and application</b>	
<b>Operating and electrical</b>		Ingress protection code	IP20 [ Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [ 0.3 J]
Input Frequency	50 or 60 Hz	<b>Initial performance (IEC compliant)</b>	
Power Factor (Min)	0.9	Initial luminous flux (system flux)	3800 lm
<b>Controls and dimming</b>		Luminous flux tolerance	+/-10%
Dimmable	Yes	Initial LED luminaire efficacy	95 lm/W
<b>Mechanical and housing</b>		Init. Corr. Color Temperature	4000 K
Housing Material	Aluminum die cast	Init. Color Rendering Index	>90
		Initial input power	40 W

## GreenUp Track

Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +40 °C
<b>Product data</b>	
Order product name	ST306T P40 940 PSD NB BK BR
Order code	911401567222

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	911401567222
Net Weight (Piece)	1.116 kg



## Dimensional drawing



ST306T P40 940 PSD NB BK BR

