



Uni Line Inground_Wall washer

BBP420 LED 27K 24V B4 L30

Uni Line Inground_Wall washer - 680 lm - 9 W - 2700 K

Philips UniLine in-ground wall washer is our latest recessed luminaire for outdoor applications. Designed to enhance surroundings in subtle or dramatic ways, this discreet luminaire offers a choice of LED colors and beam angles. So you can light up façades and landscapes with dynamic lighting effects without exposing the body of the device. And because it's compatible with Uni DMX controls and 3rd party standard DMX controls, it's easy to handle too.

Warnings and Safety

- For outdoor use only

Product data

General information		Input Frequency	
Light source color	827 warm white		- Hz
Driver included	No	Power Factor (Min)	1
Optical cover/lens type	Lens	Controls and dimming	
Control interface	-	Dimmable	No
Connection	-	Mechanical and housing	
Cable	2 cables 0.3m with connector 2-pole	Housing Material	Aluminum
Protection class IEC	Safety class III	Optical cover/lens material	Acrylate
Flammability mark	-	Color	Aluminum
CE mark	CE mark	Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm
Operating and electrical			
Input Voltage	24 V		

Uni Line Inground_Wall washer

Approval and application

Ingress protection code	IP67 [Dust penetration-protected, watertight]
Mech. impact protection code	IK10 [20 J vandal-resistant]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	680 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	75.55555555555556 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	>80
Initial input power	9 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product data

Full product code	871951452478199
Order product name	BBP420 LED 27K 24V B4 L30
EAN/UPC - Product	8719514524781
Order code	911401519981
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401519981
Net Weight (Piece)	1.490 kg



Dimensional drawing



BBP420 LED 27K 24V B4 L30

