



Uni Line Inground_Wall washer

BBP420 LED RGBNW 24V B2/HC L30 DMX

Uni Line Inground_Wall washer - 230 lm - 9 W - -

Philips UniLine in-ground wall washer is our latest recessed luminaire for outdoor applications. Designed to enhance surroundings in subtle or dramatic ways, this discreet luminaire offers a choice of LED colors and beam angles. So you can light up façades and landscapes with dynamic lighting effects without exposing the body of the device. And because it's compatible with Uni DMX controls and 3rd party standard DMX controls, it's easy to handle too.

Warnings and Safety

· For outdoor use only

Product data

| General information | |
|--------------------------|------------------|
| Light source color | RGBW |
| Driver included | No |
| Optical cover/lens type | Lens |
| Control interface | Dynamic DMX |
| Connection | - |
| Cable | - |
| Protection class IEC | Safety class III |
| Flammability mark | - |
| CE mark | CE mark |
| | |
| Operating and electrical | |
| Input Voltage | 24 V |
| | |

| Input Frequency | - Hz |
|-------------------------------------|--------------------|
| Power Factor (Min) | 1 |
| | |
| Controls and dimming | |
| Dimmable | Yes |
| | |
| Mechanical and housing | |
| Housing Material | Aluminum |
| Optical cover/lens material | Acrylate |
| Color | Aluminum |
| Dimensions (Height x Width x Depth) | NaN x NaN x NaN mm |
| | |

Datasheet, 2023, January 14 data subject to change


Uni Line Inground_Wall washer

| Approval and application | |
|-------------------------------------|--|
| Ingress protection code | IP67 [Dust penetration-protected, watertight] |
| Mech. impact protection code | IK10 [20 J vandal-resistant] |
| | |
| Initial performance (IEC compli | ant) |
| Initial luminous flux (system flux) | 230 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 25.555555555555557 lm/W |
| Init. Corr. Color Temperature | - |
| Init. Color Rendering Index | - |
| Initial input power | 9 W |
| Power consumption tolerance | +/-10% |
| | |
| Application conditions | |
| Ambient temperature range | -40 to +50 °C |

| Product data | |
|---------------------------------|------------------------------------|
| Full product code | 871951452507899 |
| Order product name | BBP420 LED RGBNW 24V B2/HC L30 DMX |
| EAN/UPC - Product | 8719514525078 |
| Order code | 911401522881 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 4 |
| Material Nr. (12NC) | 911401522881 |
| Net Weight (Piece) | 1.490 kg |
| | |



Dimensional drawing



BBP420 LED RGBNW 24V B2/HC L30 DMX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.