



UniFlood C Pro

BVP373 30LED 30K 220V 15 80W HP

UniFlood C Pro - 5375 lm - 80 W - 3000 K

Philips UniFlood C Pro offers a unique rugged elegance, with a cylindrical form and flowing lines that connect the front and back housings beautifully. This is compact architectural floodlighting design where every element has a purpose; the front section provides exceptional lighting, while the back section houses all the electrical components. Between the two, the fins dissipate heat and also serve as a decorative element. Exterior-rated, Philips UniFlood C Pro is a cost-effective, architectural LED floodlight that is designed for façade, landscape and outdoor floodlighting applications. The robust mechanical design and high-efficiency optics make it ideal for illuminating multi-story exterior façades, bridges, landmarks and monuments. Architects and designers have the freedom to explore a wide range of concepts and designs with no limitations, thanks to a range of colors, multiple spread lenses and a DMX512/RDM control option.

Warnings and Safety

- For outdoor use only

Product data

| General information | | Operating and electrical | |
|-------------------------|---------------------------------|-------------------------------|-------------------|
| Light source color | 830 warm white | Input Voltage | 220 to 240 V |
| Driver included | Yes | Input Frequency | 50 to 60 Hz |
| Optical cover/lens type | Clear glass | Power Factor (Min) | 0.9 |
| Control interface | - | Controls and dimming | |
| Connection | Flying leads/wires | Dimmable | No |
| Cable | Cable 0.5 m without plug 3-pole | Mechanical and housing | |
| Protection class IEC | Safety class I | Housing Material | Aluminum die cast |
| CE mark | CE mark | | |

UniFlood C Pro

| | |
|-----------------------------|---------------|
| Optical cover/lens material | Polycarbonate |
| Color | Dark gray |

Approval and application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial performance (IEC compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 5375 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 67 lm/W |
| Init. Corr. Color Temperature | 3000 K |
| Init. Color Rendering Index | >80 |
| Initial input power | 80 W |
| Power consumption tolerance | +/-10% |

Application conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product data

| | |
|---------------------------------|---------------------------------|
| Full product code | 872016950489999 |
| Order product name | BVP373 30LED 30K 220V 15 80W HP |
| EAN/UPC - Product | 8720169504899 |
| Order code | 911401775073 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 2 |
| Material Nr. (12NC) | 911401775073 |
| Net Weight (Piece) | 6.000 kg |



Dimensional drawing



BVP373 30LED 30K 220V 15 80W HP

