



# UniFlood C Pro

## BVP373 36LED 30K 220V 60 DMX 100W HP

UniFlood C Pro - 5125 lm - 100 W - 3000 K

Philips UniFlood C Pro offers a unique rugged elegance, with a cylindrical form and flowing lines that connect the front and back housings beautifully. This is compact architectural floodlighting design where every element has a purpose; the front section provides exceptional lighting, while the back section houses all the electrical components. Between the two, the fins dissipate heat and also serve as a decorative element. Exterior-rated, Philips UniFlood C Pro is a cost-effective, architectural LED floodlight that is designed for façade, landscape and outdoor floodlighting applications. The robust mechanical design and high-efficiency optics make it ideal for illuminating multi-story exterior façades, bridges, landmarks and monuments. Architects and designers have the freedom to explore a wide range of concepts and designs with no limitations, thanks to a range of colors, multiple spread lenses and a DMX512/RDM control option.

### Warnings and Safety

- For outdoor use only

### Product data

General information		CE mark	
Light source color	830 warm white	CE mark	
Driver included	Yes	Operating and electrical	
Optical cover/lens type	Clear glass	Input Voltage	220 to 240 V
Control interface	Dynamic DMX/RDM	Input Frequency	50 to 60 Hz
Connection	Flying leads/wires and 2 Push-in connector 4-pole	Power Factor (Min)	0.9
Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m with connector 4-pole	Controls and dimming	
Protection class IEC	Safety class I	Dimmable	Yes

# UniFlood C Pro

## Mechanical and housing

Housing Material	Aluminum die cast
Optical cover/lens material	Polycarbonate
Color	Dark gray

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	5125 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	51 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial input power	100 W
Power consumption tolerance	+/-10%

## Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product data

Full product code	872016950541499
Order product name	BVP373 36LED 30K 220V 60 DMX 100W HP
EAN/UPC - Product	8720169505414
Order code	911401775593
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401775593
Net Weight (Piece)	6.000 kg



## Dimensional drawing



BVP373 36LED 30K 220V 60 DMX 100W HP

