



GreenUp Round Highbay

BY518P LED210/NW PSU WB GC

GreenUp Round Highbay, 154 W, 21000 lm, 4000 K

The GreenUp Round Highbay range of luminaires provides the optimal balance between basic performance and price. The family covers a wide product range with a variety of options, competitive specifications, and long-term quality and reliability. The range is suitable for most industrial applications.

Product data

General Information		Number of products on MCB of 16 A type B 6	
Light source engine type	LED	Protection class IEC	Safety class I
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	21,000 lm	Dimmable	No
Correlated Color Temperature (Nom)	4000 K	Control interface	-
Luminous Efficacy (rated) (Nom)	137 lm/W		
Color rendering index (CRI)	>80	Mechanical and Housing	
Light source color	840 neutral white	Housing Material	Aluminum
Effective projected area	0.06 m ²	Optical cover material	Polycarbonate
Operating and Electrical		Housing Color	Gray
Input Voltage	220-240 V	Optical cover finish	Matte
Line Frequency	50 or 60 Hz	Overall height	99 mm
Inrush current	0.66 A	Overall diameter	305 mm
Power Consumption	154 W	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Power Factor (Fraction)	0.95	Mech. impact protection code	IK06 [1 J]
		Optical cover type	Lens

GreenUp Round Highbay

Net Weight (Piece)	2.300 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 to +45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.385, 0.380) SDCM<5
Power consumption tolerance	+/-10%

Product Data	
Order product name	BY518P LED210/NW PSU WB GC
Full product name	BY518P LED210/NW PSU WB GC
Order code	911401646407
Material Nr. (12NC)	911401646407
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

