



GreenUp Round Highbay

BY518P LED260/NW PSU WB CAU CL

GreenUp Round Highbay, 187 W, 26000 lm, 4000 K

The GreenUp Round Highbay range of luminaires provides the optimal balance between basic performance and price. The family covers a wide product range with a variety of options, competitive specifications, and long-term quality and reliability. The range is suitable for most industrial applications.

Product data

General Information		Number of products on MCB of 16 A type B 8	
Light source engine type	LED	Protection class IEC	Safety class I
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	26,000 lm	Dimmable	No
Correlated Color Temperature (Nom)	4000 K	Control interface	-
Luminous Efficacy (rated) (Nom)	139 lm/W	Mechanical and Housing	
Color rendering index (CRI)	≥80	Housing Material	Aluminium die-cast ADC1 - alloy grade (EN AC-47100)
Light source color	840 neutral white	Optical cover material	Polycarbonate
Effective projected area	0.06 m ²	Housing Color	Gray
Operating and Electrical		Optical cover finish	Matte
Input Voltage	220-240 V	Overall height	99 mm
Line Frequency	50 or 60 Hz	Overall diameter	358 mm
Inrush current	54 A	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Power Consumption	187 W	Mech. impact protection code	IK06 [1 J]
Power Factor (Fraction)	0.95	Optical cover type	Lens

GreenUp Round Highbay

Net Weight (Piece)	3.000 kg
Approval and Application	
Flammability mark	-
CE mark	No
Ambient temperature range	-20 to +45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<5
Power consumption tolerance	+/-10%

Product Data	
Order product name	BY518P LED260/NW PSU WB CAU CL
Full product name	BY518P LED260/NW PSU WB CAU CL
Full product code	871951495975000
Order code	911401645208
Material Nr. (12NC)	911401645208
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514959750
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514959750

Dimensional drawing

