



# LuxSpace Pro

## DN589B LED10/940 P8PSU D75 NB G2

LuxSpace Pro, 8.5 W, 940 neutral white, Fixed Output, IP20 |  
Finger-protected

Philips LuxSpace Pro builds on the LuxSpace family's reputation for superb performance, extremely low energy use, high visual comfort and appearance design. This next generation of reliable LED downlights comes in an elegant design with a deep, recessed architecture and increased reflector depth to highlight the smallest of details. LuxSpace Pro is also a shining example of versatility. This energy-saving LED downlight is available in a comprehensive range of configurations from 450 to 8,000 lumen, 3inch to 8inch, with the option to choose fixed, dimmable, or Interact Ready variants. This makes LuxSpace Pro the perfect 'mix and match' solution for potentially broad and extended applications that require different lighting ambiances, with one cohesive luminaire look and feel.

### Product data

General Information		Unified glare rating CEN	
Light source engine type	LED	Not applicable	
Service tag	Yes	Operating and Electrical	
Light Technical		Input Voltage	220-240 V
Luminous Flux	988 lm	Line Frequency	50 or 60 Hz
Correlated Color Temperature (Nom)	4000 K	Inrush current	20 A
Luminous Efficacy (rated) (Nom)	116 lm/W	Inrush time	50 ms
Color rendering index (CRI)	90	Power Consumption	8.5 W
Light source color	940 neutral white	Power Factor (Fraction)	0.95
Optic type	High-reflective metal reflector Medium beam 20 to 40 degrees	Number of products on MCB of 16 A type B	120
		Protection class IEC	Safety class II

# LuxSpace Pro

## Controls and Dimming

Dimmable	No
Control interface	Fixed Output

## Mechanical and Housing

Housing Material	Aluminum Alloy
Optical cover material	Polycarbonate
Housing Color	White
Optical cover finish	Frosted
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Polycarbonate Diffuser
Net Weight (Piece)	0.210 kg

## Approval and Application

CE mark	Yes
---------	-----

Ambient temperature range	-20 °C to 40 °C
---------------------------	-----------------

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	DN589B LED10/940 P8PSU D75 NB G2
Full product name	DN589B LED10/940 P8PSU D75 NB G2
Order code	911401589243
Material Nr. (12NC)	911401589243
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

## Dimensional drawing

