



LuxSpace Pro

DN590B LED16/940 P14PSD D100 WB G2

LuxSpace Pro, 14 W, 940 neutral white, DALI, IP20 | Finger-protected

Philips LuxSpace Pro builds on the LuxSpace family's reputation for superb performance, extremely low energy use, high visual comfort and appearance design. This next generation of reliable LED downlights comes in an elegant design with a deep, recessed architecture and increased reflector depth to highlight the smallest of details. LuxSpace Pro is also a shining example of versatility. This energy-saving LED downlight is available in a comprehensive range of configurations from 450 to 8,000 lumen, 3inch to 8inch, with the option to choose fixed, dimmable, or Interact Ready variants. This makes LuxSpace Pro the perfect 'mix and match' solution for potentially broad and extended applications that require different lighting ambiances, with one cohesive luminaire look and feel.

Product data

General Information		Unified glare rating CEN	
Light source engine type	LED	20	
Service tag	Yes	Operating and Electrical	
Light Technical		Input Voltage	220-240 V
Luminous Flux	1,574 lm	Line Frequency	50 or 60 Hz
Correlated Color Temperature (Nom)	4000 K	Inrush current	16.5 A
Luminous Efficacy (rated) (Nom)	113 lm/W	Inrush time	177 ms
Color rendering index (CRI)	90	Power Consumption	14 W
Light source color	940 neutral white	Power Factor (Fraction)	0.9
Optic type	High-reflective metal reflector Wide beam 40 to 80 degrees	Number of products on MCB of 16 A type B	36
		Protection class IEC	Safety class II

LuxSpace Pro

Controls and Dimming

Dimmable	Yes
Control interface	DALI
Maximum dim level	1%

Mechanical and Housing

Housing Material	Aluminum Alloy
Optical cover material	Polycarbonate
Housing Color	White
Optical cover finish	Frosted
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Optical cover type	Polycarbonate Diffuser
Net Weight (Piece)	0.340 kg

Approval and Application

CE mark	Yes
---------	-----

Ambient temperature range	-20 °C to 40 °C
---------------------------	-----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	DN590B LED16/940 P14PSD D100 WB G2
Full product name	DN590B LED16/940 P14PSD D100 WB G2
Order code	911401592143
Material Nr. (12NC)	911401592143
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

