



LuxSpace Pro

DN590B LED18/830 P14PSD D150 WB G2

LuxSpace Pro, 13.6 W, 830 warm white, DALI, IP20 | Finger-protected

Philips LuxSpace Pro builds on the LuxSpace family's reputation for superb performance, extremely low energy use, high visual comfort and appearance design. This next generation of reliable LED downlights comes in an elegant design with a deep, recessed architecture and increased reflector depth to highlight the smallest of details. LuxSpace Pro is also a shining example of versatility. This energy-saving LED downlight is available in a comprehensive range of configurations from 450 to 8,000 lumen, 3inch to 8inch, with the option to choose fixed, dimmable, or Interact Ready variants. This makes LuxSpace Pro the perfect 'mix and match' solution for potentially broad and extended applications that require different lighting ambiances, with one cohesive luminaire look and feel.

Product data

| General Information | | Unified glare rating CEN | |
|------------------------------------|---|--|-----------------|
| Light source engine type | LED | | 17 |
| Service tag | Yes | | |
| Light Technical | | Operating and Electrical | |
| Luminous Flux | 1,713 lm | Input Voltage | 220-240 V |
| Correlated Color Temperature (Nom) | 3000 K | Line Frequency | 50 or 60 Hz |
| Luminous Efficacy (rated) (Nom) | 126 lm/W | Inrush current | 16.5 A |
| Color rendering index (CRI) | 80 | Inrush time | 177 ms |
| Light source color | 830 warm white | Power Consumption | 13.6 W |
| Optic type | High-reflective metal reflector Wide beam 40 to 80 degrees | Power Factor (Fraction) | 0.9 |
| | | Number of products on MCB of 16 A type B | 36 |
| | | Protection class IEC | Safety class II |

LuxSpace Pro

Controls and Dimming

| | |
|-------------------|------|
| Dimmable | Yes |
| Control interface | DALI |
| Maximum dim level | 1% |

Mechanical and Housing

| | |
|------------------------------|-------------------------|
| Housing Material | Aluminum Alloy |
| Optical cover material | Polycarbonate |
| Housing Color | White |
| Optical cover finish | Frosted |
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK03 [0.3 J] |
| Optical cover type | Polycarbonate Diffuser |
| Net Weight (Piece) | 0.610 kg |

Approval and Application

| | |
|---------|-----|
| CE mark | Yes |
|---------|-----|

| | |
|---------------------------|-----------------|
| Ambient temperature range | -20 °C to 40 °C |
|---------------------------|-----------------|

Initial Performance (IEC Compliant)

| | |
|-----------------------------|--------|
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |

Product Data

| | |
|---------------------------------|------------------------------------|
| Order product name | DN590B LED18/830 P14PSD D150 WB G2 |
| Full product name | DN590B LED18/830 P14PSD D150 WB G2 |
| Order code | 911401597243 |
| Material Nr. (12NC) | 911401597243 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |

Dimensional drawing

