



# GreenPerform Panel RC099V G3

## RC099V G3 LED29/950 PSD W60L60 OC CAU HE

GreenPerform Panel RC099V G3, 125 lm/W, 950, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Protection class IEC	
Light source engine type	LED	Safety class II	
Service tag	Yes	Controls and Dimming	
Light Technical		Dimmable	DALI
Luminous Flux	2,900 lm	Control interface	DALI
Correlated Color Temperature (Nom)	5000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	125 lm/W	Housing Material	Metal
Color rendering index (CRI)	>90	Optical cover material	Polystyrene
Light source color	950	Housing Color	White RAL 9003
Operating and Electrical		Optical cover finish	Opal
Input Voltage	220-240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 or 60 Hz	Mech. impact protection code	IK03 [0.3 J]
Power Consumption	23.2 W	Optical cover type	Opal
Power Factor (Fraction)	0.9	Net Weight (Piece)	1.790 kg
Number of products on MCB of 16 A type B 17			

# GreenPerform Panel RC099V G3

## Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	RC099V G3 LED29/950 PSD W60L60 OC CAU HE
--------------------	---

Full product name	RC099V G3 LED29/950 PSD W60L60 OC CAU HE
Order code	911401520543
Material Nr. (12NC)	911401520543
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

## Dimensional drawing

