



# GreenPerform Panel RC099V G3

## RC099V G3 LED29/965 PSU W30L120 OC CAUHE

GreenPerform Panel RC099V G3, 125 lm/W, 965 cool daylight

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Protection class IEC	
Light source engine type	LED	Safety class II	
Service tag	Yes	Controls and Dimming	
<b>Light Technical</b>		Dimmable	No
Luminous Flux	2,900 lm	Control interface	-
Correlated Color Temperature (Nom)	6500 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	125 lm/W	Housing Material	Metal
Color rendering index (CRI)	>90	Optical cover material	Polystyrene
Light source color	965 cool daylight	Housing Color	White RAL 9003
<b>Operating and Electrical</b>		Optical cover finish	Opal
Input Voltage	220-240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 or 60 Hz	Mech. impact protection code	IK03 [0.3 J]
Power Consumption	23.2 W	Optical cover type	Opal
Power Factor (Fraction)	0.9	Net Weight (Piece)	1.940 kg
Number of products on MCB of 16 A type B	17		

# GreenPerform Panel RC099V G3

## Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	RC099V G3 LED29/965 PSU W30L120 OC CAUHE
--------------------	---

Full product name	RC099V G3 LED29/965 PSU W30L120 OC CAUHE
Order code	911401512743
Material Nr. (12NC)	911401512743
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

## Dimensional drawing

