



GreenPerform Panel RC099V G3

RC099V G3 LED32/965 PSU W60L60 OC CAU HE

GreenPerform Panel RC099V G3, 125 lm/W, 965 cool daylight

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

Product data

General Information		Protection class IEC	Safety class II
Light source engine type	LED	Controls and Dimming	
Service tag	Yes	Dimmable	No
Light Technical		Control interface	-
Luminous Flux	3,200 lm	Mechanical and Housing	
Correlated Color Temperature (Nom)	6500 K	Housing Material	Metal
Luminous Efficacy (rated) (Nom)	125 lm/W	Optical cover material	Polystyrene
Color rendering index (CRI)	>90	Housing Color	White RAL 9003
Light source color	965 cool daylight	Optical cover finish	Opal
Operating and Electrical		Ingress protection code	IP20 [Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [0.3 J]
Line Frequency	50 or 60 Hz	Optical cover type	Opal
Power Consumption	25.6 W	Net Weight (Piece)	1.790 kg
Power Factor (Fraction)	0.9		
Number of products on MCB of 16 A type B	17		

GreenPerform Panel RC099V G3

Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Product Data

Order product name	RC099V G3 LED32/965 PSU W60L60 OC CAU HE
--------------------	---

Full product name	RC099V G3 LED32/965 PSU W60L60 OC CAU HE
Order code	911401513643
Material Nr. (12NC)	911401513643
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Dimensional drawing

