



# GreenPerform Panel RC099V G3

## RC099V G3 LED34/850 PSD W30L120 OC CAU

GreenPerform Panel RC099V G3, 105 lm/W, 850 neutral white, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Number of products on MCB of 16 A type B 17	
Light source engine type	LED	Protection class IEC	Safety class II
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	3,400 lm	Dimmable	DALI
Correlated Color Temperature (Nom)	5000 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	105 lm/W		
Color rendering index (CRI)	>80	Mechanical and Housing	
Light source color	850 neutral white	Housing Material	Metal
Operating and Electrical		Optical cover material	Polystyrene
Input Voltage	220-240 V	Housing Color	White RAL 9003
Line Frequency	50 or 60 Hz	Optical cover finish	Opal
Power Consumption	32.7 W	Ingress protection code	IP20 [Finger-protected]
Power Factor (Fraction)	0.9	Mech. impact protection code	IK03 [0.3 J]
		Optical cover type	Opal

# GreenPerform Panel RC099V G3

Net Weight (Piece)	1.940 kg
--------------------	----------

## Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	RC099V G3 LED34/850 PSD W30L120 OC CAU
--------------------	-------------------------------------------

Full product name	RC099V G3 LED34/850 PSD W30L120 OC CAU
Order code	911401595642
Material Nr. (12NC)	911401595642
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

## Dimensional drawing

