



RC099V G3 LED34/865 PSD W30L120 OC CAU

GreenPerform Panel RC099V G3, 105 lm/W, 865 cool daylight, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600,300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

Product data

General Information	
Light source engine type	LED
Service tag	Yes
Light Technical	
Luminous Flux	3,400 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	>80
Light source color	865 cool daylight
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	32.7 W
Power Factor (Fraction)	0.9

Number of products on MCB of 16 A type B 17		
Protection class IEC	Safety class II	
Controls and Dimming		
Dimmable	DALI	
Control interface	DALI	
Mechanical and Housing		
Housing Material	Metal	
Optical cover material	Polystyrene	
Housing Color	White RAL 9003	
Optical cover finish	Opal	
Ingress protection code	IP20 [Finger-protected]	
Mech. impact protection code	IKO3 [0.3 J]	
Optical cover type	Opal	

Datasheet, 2024, October 23 data subject to change

GreenPerform Panel RC099V G3

Net Weight (Piece)	1.940 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 °C to 45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	RC099V G3 LED34/865 PSD W30L120 OC
	CAU

Full product name	RC099V G3 LED34/865 PSD W30L120 OC
	CAU
Order code	911401595542
Material Nr. (12NC)	911401595542
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Dimensional drawing



