



# GreenPerform Panel RC099V G3

## RC099V G3 LED36/950 PSU W30L120 OC HE

GreenPerform Panel RC099V G3, 125 lm/W, 950

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Number of products on MCB of 16 A type B 17	
Light source engine type	LED		
Light Technical		Temperature	
Luminous Flux	3,400 lm	Ambient temperature range	-20 °C to 45 °C
Luminous Efficacy (rated) (Nom)	125 lm/W	Controls and Dimming	
Correlated Color Temperature (Nom)	5000 K	Dimmable	No
Color rendering index (CRI)	>90	Control interface	-
Light source color	950	Mechanical and Housing	
Optical cover type	Opal	Housing Material	Metal
Operating and Electrical		Optical cover material	Polystyrene
Input Voltage	220-240 V	Housing Color	White RAL 9003
Line Frequency	50 or 60 Hz	Optical cover finish	Opal
Power Consumption	27.2 W	Approval and Application	
Power Factor (Fraction)	0.9	Ingress protection code	IP20 [Finger-protected]

# GreenPerform Panel RC099V G3

Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class II
CE mark	Yes
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%
<b>Product Data</b>	
Order product name	RC099V G3 LED36/950 PSU W30L120 OC HE

Full product name	RC099V G3 LED36/950 PSU W30L120 OC HE
Order code	911401510343
Material Nr. (12NC)	911401510343
Numerator - Quantity Per Pack	1
Net Weight (Piece)	1.940 kg
Numerator - Packs per outer box	4

## Dimensional drawing

