



GreenPerform Panel RC099V G3

RC099V G3 LED38/840 PSD W30L120

GreenPerform Panel RC099V G3, 125 lm/W, 840 neutral white, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600,300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

Product data

General Information		Number of products on MCB of 16 A type B	
Light source engine type	LED		17
Service tag	Yes	Protection class IEC	Safety class II
Light Technical		Controls and Dimming	
Luminous Flux	3,800 lm	Dimmable	DALI
Correlated Color Temperature (Nom)	4000 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	125 lm/W	Mechanical and Housing	
Color rendering index (CRI)	>80	Housing Material	Metal
Light source color	840 neutral white	Optical cover material	Polystyrene
Operating and Electrical		Housing Color	White RAL 9003
Input Voltage	220-240 V	Optical cover finish	Opal
Line Frequency	50 or 60 Hz	Ingress protection code	IP20 [Finger-protected]
Power Consumption	30.4 W	Mech. impact protection code	IK03 [0.3 J]
Power Factor (Fraction)	0.9	Optical cover type	Opal

GreenPerform Panel RC099V G3

Net Weight (Piece)	1.940 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 °C to 45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Product Data	
Order product name	RC099V G3 LED38/840 PSD W30L120
Full product name	RC099V G3 LED38/840 PSD W30L120
Order code	911401594642
Material Nr. (12NC)	911401594642
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Dimensional drawing

