



GreenPerform Panel RC099V G3

RC099V G3 LED48/865 PSU W30L120 OC

GreenPerform Panel RC099V G3, 120 lm/W, 865 cool daylight

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

Product data

General Information		Number of products on MCB of 16 A type B 17	
Light source engine type	LED	Protection class IEC	Safety class II
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	4,800 lm	Dimmable	No
Correlated Color Temperature (Nom)	6500 K	Control interface	-
Luminous Efficacy (rated) (Nom)	120 lm/W		
Color rendering index (CRI)	>80	Mechanical and Housing	
Light source color	865 cool daylight	Housing Material	Metal
Unified glare rating CEN	Not applicable	Optical cover material	Polystyrene
		Housing Color	White RAL 9003
		Optical cover finish	Opal
Operating and Electrical		Ingress protection code	IP20 [Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [0.3 J]
Line Frequency	50 or 60 Hz	Optical cover type	Opal
Power Consumption	40 W	Net Weight (Piece)	1.940 kg
Power Factor (Fraction)	0.9		

GreenPerform Panel RC099V G3

Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Product Data

Order product name	RC099V G3 LED48/865 PSU W30L120 OC
--------------------	------------------------------------

Full product name	RC099V G3 LED48/865 PSU W30L120 OC
Full product code	692382862018999
Order code	911401509443
Material Nr. (12NC)	911401509443
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828620189
Numerator - Packs per outer box	4
EAN/UPC - Case	6923828620189

Dimensional drawing

