



# GreenPerform Panel RC099V G3

## RC099V G3 LED50/840 PSD W60L120 OC CAU

GreenPerform Panel RC099V G3, 110 lm/W, 840 neutral white, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Number of products on MCB of 16 A type B 17	
Light source engine type	LED	Protection class IEC	Safety class II
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	5,000 lm	Dimmable	DALI
Correlated Color Temperature (Nom)	4000 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	110 lm/W		
Color rendering index (CRI)	>80	Mechanical and Housing	
Light source color	840 neutral white	Housing Material	Metal
Operating and Electrical		Optical cover material	Polystyrene
Input Voltage	220-240 V	Housing Color	White RAL 9003
Line Frequency	50 or 60 Hz	Optical cover finish	Opal
Power Consumption	45.5 W	Ingress protection code	IP20 [Finger-protected]
Power Factor (Fraction)	0.9	Mech. impact protection code	IK03 [0.3 J]
		Optical cover type	Opal

# GreenPerform Panel RC099V G3

Net Weight (Piece)	3.390 kg	Full product name	RC099V G3 LED50/840 PSD W60L120 OC CAU
<b>Approval and Application</b>		Order code	911401595342
CE mark	Yes	Material Nr. (12NC)	911401595342
Ambient temperature range	-20 °C to 45 °C	Numerator - Quantity Per Pack	1
<b>Initial Performance (IEC Compliant)</b>		Numerator - Packs per outer box	2
Luminous flux tolerance	-10% / +10%		
Power consumption tolerance	+/-10%		
<b>Product Data</b>			
Order product name	RC099V G3 LED50/840 PSD W60L120 OC CAU		

## Dimensional drawing

