



# GreenPerform Panel RC099V G3

## RC099V G3 LED50/840 PSU W60L120 OC HE

GreenPerform Panel RC099V G3, 135 lm/W, 840 neutral white

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

### Product data

General Information		Protection class IEC	Safety class II
Light source engine type	LED	<b>Controls and Dimming</b>	
Service tag	Yes	Dimmable	No
<b>Light Technical</b>		Control interface	-
Luminous Flux	5,000 lm	<b>Mechanical and Housing</b>	
Correlated Color Temperature (Nom)	4000 K	Housing Material	Metal
Luminous Efficacy (rated) (Nom)	135 lm/W	Optical cover material	Polystyrene
Color rendering index (CRI)	>80	Housing Color	White RAL 9003
Light source color	840 neutral white	Optical cover finish	Opal
<b>Operating and Electrical</b>		Ingress protection code	IP20 [Finger-protected]
Input Voltage	220-240 V	Mech. impact protection code	IK03 [0.3 J]
Line Frequency	50 or 60 Hz	Optical cover type	Opal
Power Consumption	37 W	Net Weight (Piece)	3.390 kg
Power Factor (Fraction)	0.9		
Number of products on MCB of 16 A type B	17		

# GreenPerform Panel RC099V G3

## Approval and Application

CE mark	Yes
Ambient temperature range	-20 °C to 45 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	RC099V G3 LED50/840 PSU W60L120 OC HE
--------------------	--

Full product name	RC099V G3 LED50/840 PSU W60L120 OC HE
Order code	911401593342
Material Nr. (12NC)	911401593342
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

## Dimensional drawing

