



GreenPerform Panel RC099V G3

RC099V G3 LED50/850 PSD W60L120 OC CAU

GreenPerform Panel RC099V G3, 110 lm/W, 850 neutral white, DALI

GreenPerform panel RC099V G3 is an affordable LED panel delivering comfortable light with excellent uniformity. It offers 3 types, 600x600, 300x1200, and 600x1200mm with max: 140lm/w. Its UGR19 brings more visual comfort in the office. Equipped with Dali, Interact and EcoSet, RC099V G2 offers easy connection to control system to bring better energy saving.

Product data

General Information		Number of products on MCB of 16 A type B 17	
Light source engine type	LED	Protection class IEC	Safety class II
Service tag	Yes		
Light Technical		Controls and Dimming	
Luminous Flux	5,000 lm	Dimmable	DALI
Correlated Color Temperature (Nom)	5000 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	110 lm/W		
Color rendering index (CRI)	>80	Mechanical and Housing	
Light source color	850 neutral white	Housing Material	Metal
Operating and Electrical		Optical cover material	Polystyrene
Input Voltage	220-240 V	Housing Color	White RAL 9003
Line Frequency	50 or 60 Hz	Optical cover finish	Opal
Power Consumption	45.5 W	Ingress protection code	IP20 [Finger-protected]
Power Factor (Fraction)	0.9	Mech. impact protection code	IK03 [0.3 J]
		Optical cover type	Opal

GreenPerform Panel RC099V G3

Net Weight (Piece)	3.390 kg
Approval and Application	
CE mark	Yes
Ambient temperature range	-20 °C to 45 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	RC099V G3 LED50/850 PSD W60L120 OC CAU

Full product name	RC099V G3 LED50/850 PSD W60L120 OC CAU
Order code	911401595242
Material Nr. (12NC)	911401595242
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

