



# GreenUp Grid

## GD309B 3\*P20 930 PSU-E MB

GreenUp Grid, 54 W, 66 W, 930 warm white, IP20 | Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenSpace Grid product family offers a complete range of options with comprehensive control availability, optical solutions and powerful lumen outputs, meanwhile ensures the product reliability and quality within compact luminaire body.

### Product data

| General Information                      |                | Protection class IEC         |                         |
|--|----------------|------------------------------|-------------------------|
| Light source engine type                 | LED            |                              | Safety class II         |
| Light Technical                          |                | Controls and Dimming         |                         |
| Luminous Flux                            | 5,400 lm       | Dimmable                     | No                      |
| Correlated Color Temperature (Nom)       | 3000 K         | Control interface            | -                       |
| Luminous Efficacy (rated) (Nom)          | 90 lm/W        | Mechanical and Housing       |                         |
| Color rendering index (CRI)              | >90            | Housing Material             | Aluminum Alloy          |
| Light source color                       | 930 warm white | Optical cover material       | Acrylate                |
| Operating and Electrical                 |                | Housing Color                | White                   |
| Input Voltage                            | 200 to 240 V   | Optical cover finish         | Frosted                 |
| Line Frequency                           | 50 to 60 Hz    | Ingress protection code      | IP20 [Finger-protected] |
| Power Consumption                        | 54 66 W        | Mech. impact protection code | IK03 [0.3 J]            |
| Power Factor (Fraction)                  | 0.9            | Optical cover type           | Acrylate                |
| Number of products on MCB of 16 A type B | -              | Net Weight (Piece)           | 2.030 kg                |

# GreenUp Grid

## Approval and Application

|                           |               |
|---------------------------|---------------|
| CE mark                   | No            |
| Ambient temperature range | -20 to +40 °C |

## Initial Performance (IEC Compliant)

|                             |        |
|-----------------------------|--------|
| Luminous flux tolerance     | +/-10% |
| Power consumption tolerance | +/-10% |

## Product Data

|                    |                           |
|--------------------|---------------------------|
| Order product name | GD309B 3*P20 930 PSU-E MB |
|--------------------|---------------------------|

|                                 |                           |
|---------------------------------|---------------------------|
| Full product name               | GD309B 3*P20 930 PSU-E MB |
| Full product code               | 872016953089899           |
| Order code                      | 911401511312              |
| Material Nr. (12NC)             | 911401511312              |
| Numerator - Quantity Per Pack   | 1                         |
| EAN/UPC - Product/Case          | 8720169530898             |
| Numerator - Packs per outer box | 4                         |
| EAN/UPC - Case                  | 8720169542389             |

## Dimensional drawing

